

China

CMC

COA

C2h2

China Cylinder Gas Best Price High Quality 40L C2h2 Acetylene Gas

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1kg
- Price: US \$25/PC
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 2000 Pcs/Month

Product Specification

• Product Name: Acetylene Gas Cylinder Standard: GB/ISO/DOT -81.8 ºC • Melting Point: -83.4 ºC • Boiling Point: • Cylinder Pressure: 15MPa • Model No.: Acetylene Gas 40L Specification: CMC Trademark: • Origin: China • HS Code: 29012920 • Supply Ability: 2000cylinder/Month 74-86-2 • CAS No.: Formula: C2h2

200-816-9

Industrial Pure Air



高纯乙炔

More Images

• EINECS:

Constituent:









Product Description

Product Description

Acetylene gas (C2H2) is a highly flammable hydrocarbon gas that consists of two carbon atoms bonded to two hydrogen atoms. It is commonly used in various industrial applications, particularly in welding and cutting processes. Here are some key points about acetylene gas: Properties: Acetylene gas is colorless and has a distinct odor similar to garlic or rotten cabbage. It is highly flammable and can form explosive mixtures with air. Acetylene gas is lighter than air, so it tends to rise and disperse in the atmosphere.

Production: Acetylene gas is produced through the reaction of calcium carbide (CaC2) with water (H2O) in a process called hydrolysis: $CaC2 + 2H2O \rightarrow C2H2 + Ca(OH)2$

This reaction generates acetylene gas along with calcium hydroxide as a byproduct.

Uses: Acetylene gas has several important applications:

Welding and Cutting: Acetylene gas is widely used as a fuel in oxyacetylene welding and cutting torches. When mixed with oxygen and ignited, it produces a high-temperature flame that can reach around 3,500 degrees Celsius (6,332 degrees Fahrenheit), suitable for melting and joining metals.

Chemical Synthesis: Acetylene gas serves as a building block for the synthesis of various organic compounds. It is used in the production of plastics, solvents, pharmaceuticals, and other chemicals.

Lighting: Historically, acetylene gas was used in acetylene lamps for portable lighting. However, these lamps have largely been replaced by electric lighting systems.

Calibration Gas: Acetylene gas is sometimes used as a calibration gas in analytical instruments due to its well-defined properties.

Safety Considerations: Acetylene gas is highly flammable and can form explosive mixtures with air. It is sensitive to ignition sources such as sparks, flames, or electrical equipment. Acetylene gas cylinders should be stored and handled with care, following specific safety guidelines. It is crucial to avoid rough handling, exposure to excessive heat, and incompatible materials that can react with acetylene gas.

When working with acetylene gas, it is essential to follow proper safety protocols, including using appropriate gas handling equipment, ensuring proper ventilation, and being aware of the risks associated with its flammability and potential for explosive decomposition.

Basic	Info
Dasic	millo.

Dasic IIIIO.			
Model NO.	C2H2	Un	1001
Hazard Class	2.1	Label	Common
Analysis Report	Certificate of Conformity	Chemical Formula	C2h2
Purity	98%	Widely Used	Electronically Conducting Plastics
Product Name	Acetylene	Transport Package	Cylinder/Tank
Specification	40L or others	Trademark	CMC
Origin	Suzhou, Jiangsu, China	HS Code	29012920
Production Capacity	2000cylinder/Month		

Specification:

Gas	Acetylene		Chemical Formula	C2H2
Hazard Class	2.1		Molecular Weight	26.038
CAS	74-86-2		UN	1001
Boiling Point	at 1.013 bar [ºC]	-84.15	at 14.5 psi, [ºF]	-241.17
Density	at 1.013 bar,15ºC, [kg/m³]	1.109	at 1 atm., 70ºF, [lb/ft³]	0.068

Detailed Photos



SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.



III Shanghai Kemike Chemical Co.,Ltd

+86 18762990415

williamchen@cmc-chemical.com

@ gascylindertank.com